

FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

Grey, 2 m

CORNING

The application-neutral FutureCom™ S500 category 6_A patch cords have four individual foil-shielded pairs (PiMF) and an additional braid shield (S/FTP). They are assembled with a shielded RJ45 connectors on each end. The zero halogen patch cords (LSZH) are non-corrosive according to IEC 60754-2 (FRNC) and EN 50267, low smoke according to IEC 61034 and EN 50268 and flame retardant according to IEC 60332-1, Category B and EN 50266-2-1. FutureCom™ S500 patch cords provide additional latch protection.

They are available in various lengths and colours.

Features

- S/FTP flex cable, Category 7
- Application-neutral due to using all four pairs of RJ45 connectors
- Minimum surface transfer impedance of cable (<10 mΩ/m at 10 MHz)
- Outstanding transmission characteristics according to 10GBase-T
- Additional latch protection
- Category 6_A



Specifications

General Specifications	
Cable Assembly Type	Patch Cords
Environment	Indoor
Cable Type	S/FTP
Halogen-free	Yes
Category	6 _A

Design - Connector A	
Connector Type	RJ45 - 8/8



FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

Grey, 2 m

CORNING

Mechanical Specifications - Connector A

Durability	750 Cycles
------------	------------

Electrical Specifications - Connector

Insulation resistance	≥ 5000 MΩ
-----------------------	-----------

Design - Connector B

Copper Connector Type - B	RJ45 - 8/8
---------------------------	------------

Cable Design

Min. Bend Radius Installation	40 mm
Min. Bend Radius Operation	30 mm
Outer diameter	5.8 mm
Outer jacket material	LSZH/FRNC
Outer jacket colour	Grey

Mechanical characteristics

Conductor insulation	Braided shield Individual pair shield (PiMF)
Operating temperature	-20 °C to 60 °C

FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

Grey, 2 m

CORNING

Electrical characteristics (at 20°C)

Max. loop resistance	290 Ω/km
DC resistance unbalance	2 %
Impedance Z_0 at 0-100 MHz	100 Ω +- 15%
Impedance Z_0 at 101-250 MHz	100 Ω +- 18%
Impedance z_0 at 251-600 MHz	100 Ω +- 25%
Surface transfer impedance	< 10 mΩ/m per meter at 10 MHz
Mutual capacity	43 pF/m
Earth coupling at 0.001 MHz	1600
Propagation delay >=10 MHz	4.3 ns/m
Delay skew	20 ns/100 m

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Order Number	CCAAGB-G1002-A020-C0
Product Description	FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector, grey, 2 m
Weight	0.096 kg
Length	2 m

Shipping Information

Units per Delivery	1/1
--------------------	-----

Corning Cable Systems GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, Germany

TEL: 00800-2676-4641 (00800-CORNING1) · FAX: +49-30-5303-2335 · www.corning.com/cablesystems/emea

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/emea/trademarks. Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.