

Pretium EDGE® Solutions Trunk Cable, OM3, Low-Loss, MTP® to MTP, 24 fibres

500/500 mm leg lengths, no pulling grip, 10 m

CORNING

Corning Cable Systems LANscape® Pretium EDGE® (Evolved-Density, Growth-Enabled) Solutions are high density pre-terminated optical cabling systems that simplify installation and improve performance in data centre environments. Pretium EDGE Solutions provide increased system density and offer the highest port density in the market. The modular system approach with pre-terminated components allows for reduced installation time and faster moves, adds and changes (MACs).

Corning Cable Systems' factory-terminated solutions provide improved system performance, ensure component compatibility and yield consistent quality.

Pre-terminated trunk cabling systems fitted with a factory-installed protective pulling grip are routed through the cabling pathways and spaces. Once deployed, the pulling grip is removed and the MTP® connectors on both ends are plugged into connector panels or modules.

High-density MTP connector-based trunk systems plug into breakout modules or harnesses for a simple, fast-to-deploy, modular solution with easy scalability.

Features and Benefits

Provide 12 to 144 fibre connectivity

Cables are: Low smoke (IEC 61034) and zero-halogen (IEC 60754-1), flame retardant to IEC 60332-3 and non-corrosive to IEC 60754-2 (FRNC)

Utilize MTP connectors

- Small Form Factor
 - 12-fibre push/pull optical connectors
 - minimize errors and reduce space
-

Allow for lower bend radii and smaller slack loops

Enable up to 6x the cable tray capacity over traditional bulkier cabling solutions

Save up to 65 percent space, minimize cable tray weight and improve air flow

Meet the highest skew criteria for 100G

Feature round furcation legs that provide easy routing and improved storage

Feature small-profile furcation plugs

- allow stress-free cable mounting
- leave no legs outside the housing
- are shipped with strain-relief mounting cradles

Pretium EDGE® Solutions Trunk Cable, OM3, Low-Loss, MTP® to MTP, 24 fibres

500/500 mm leg lengths, no pulling grip, 10 m

CORNING

Features and Benefits

Are available with optional flexible pulling grips that

- allow easy installation around corners
- allow trunk pull through conduits up to 450 N
- provide complete protection for connectors

Standards

Intermateability TIA/EIA-604-5 / TIA/
EIA-604-5

Specifications

General Specifications

Flame Rating	LSZH/FRNC
Fibre Category	50 µm MM (OM3)
Cable Assembly Type	Multi Fibre

Temperature Range

Operation	-20 °C to 60 °C
Installation and assembly	-5 °C to 50 °C
Storage	-25 °C to 70 °C

Design - Connector A

Connector Type	MTP® (non-pinned)
Ferrule	Composite
Polish	PC
Housing material	Composite
Housing Colour	Turquoise
Boot Type	Individual
Boot Colour	Black
Keyed (security)	No

Pretium EDGE® Solutions Trunk Cable, OM3, Low-Loss, MTP® to MTP, 24 fibres

500/500 mm leg lengths, no pulling grip, 10 m

CORNING

Mechanical Specifications - Connector A

Durability	≤ 0.2 dB 200 rematings, FOTP-21
Tensile strength jacketed cable	44 N

Optical Specifications - Connector A

Insertion Loss, Typical	0.35 dB
Insertion loss, max.	≤ 0.35 dB

Design - Connector B

Connector Type	MTP® (non-pinned)
Ferrule	Composite
Polish	PC
Housing material	Composite
Housing Colour	Turquoise
Boot Type	Individual
Boot Colour	black
Keyed (security)	No

Mechanical Specifications - Connector B

Durability	≤ 0.2 dB 200 rematings, FOTP-21
Tensile strength jacketed cable	44 N

Optical Specifications - Connector B

Insertion Loss, Typical	0.35 dB
Insertion loss, max.	≤ 0.35 dB

Pretium EDGE® Solutions Trunk Cable, OM3, Low-Loss, MTP® to MTP, 24 fibres

500/500 mm leg lengths, no pulling grip, 10 m

CORNING

Cable Design

Fibre Count	24
Outer diameter	5.2 mm
Outer jacket colour	Turquoise
Outer jacket material	LSZH/FRNC
Min. Bend Radius Installation	52 mm
Min. Bend Radius Operation	26 mm
Crush Resistance	750 N/10cm
Tensile strength	600 N

Furcation - Connector A

Legs Count	2
Leg Length	500 mm for EDGE-04U-RDH
Leg Diameter	2.9 mm
Fibre Count	24
Plug Type	Size 1 Pretium EDGE®
Plug Dimensions	107.6 x 14.7 x 14.7 mm

Furcation - Connector B

Legs Count	2
Leg Length	500 mm for EDGE-04U-RDH
Leg Diameter	2.9 mm
Fibre Count	24
Plug Type	Size 1 Pretium EDGE®
Plug Dimensions	107.6 x 14.7 x 14.7 mm

Pulling Grip - Connector A

Pulling Grip - Connector A	No
----------------------------	----

Pulling Grip - Connector B

Pulling Grip - Connector B	No
----------------------------	----

Pretium EDGE® Solutions Trunk Cable, OM3, Low-Loss, MTP® to MTP, 24 fibres

500/500 mm leg lengths, no pulling grip, 10 m

CORNING

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Fibre Specifications

Optical Characteristics (cabled)

Fibre name	G50/125 Pretium 300 ULTRA-BEND 7.5
Fibre Core Diameter	50 µm
Fibre Type	Multimode
Fibre Category	OM3
Wavelengths	850 nm / 1300 nm
Maximum Attenuation	2.8 dB/km / 1 dB/km
Typical attenuation	2.4 dB/km / 0.8 dB/km
Min. Overfilled Launch (OFL) Bandwidth	1500 MHz*km / 500 MHz*km
Minimum Effective Modal Bandwidth (EMB)	2000 MHz*km / -
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	300 m / 333 m
Induced attenuation @ 7.5 mm radius	< 0.2 dB / -
Standards in Compliance	TIA/EIA 492AAAC-A, Tested with minEMBc method to TIA/EIA 455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0 and IEC 60793-1-49 Ed.2.0, ITU-T G651, ISO/IEC 11801 Cat. OM3
Fibre Code	H

Notes: 1) 50 µm multimode fibre macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel
2) Meets 0.75 ns optical skew when used in all Corning Cable Systems Plug & Play™/Pretium EDGE® Systems Solutions
3) Improved attenuation and bandwidth options available
4) Bend-insensitive single-mode fibres available on request
5) Contact a Corning Cable Systems Customer Service Representative for additional information

Ordering Information

Part Number	Z757524TLZ55U010M
Product Description	Pretium EDGE® Solutions Trunk Cable, OM3, Low-Loss, MTP® Connector to MTP Connector, 24 fibres, 500/500 mm leg lengths, no pulling grip, 10 m
Length	10 m

Pretium EDGE® Solutions Trunk Cable, OM3, Low-Loss, MTP® to MTP, 24 fibres

500/500 mm leg lengths, no pulling grip, 10 m

CORNING

Shipping Information

Packing type	Cardboard box
Packing contents	2x Pretium EDGE® clip size 1 test report
Units per Delivery	1/1



Corning Cable Systems GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, Germany

TEL: 00800-2676-4641 (00800-CORNING1) · FAX: +49-30-5303-2335 · www.corning.com/cablesystems/emea

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/emea/trade-marks. Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.