

EDGE8® MTP® Trunk Cable Bend-improved single-mode (OS2), 8F MTP (pinned) Connector to 8F MTP (pinned) Connector, 8F, with 840 mm legs, no pulling grip, 30 m

CORNING

Part Number:
ZE7E708GLZDDU030M

EDGE8™ trunks utilize an 8-fibre push/pull optical connector that is pinned on both ends of the cable. The trunks are shipped with strain-relief clips that allow for tool-less installation in EDGE8 housings. The grip can be pulled using up to 100 lbs of pulling tension while providing complete protection for the connectors. All trunks greater than 75 ft are packaged on a plastic corrugated reel for easy installation.

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves the cable tray fill ratio and allows for improved airflow

Low-loss connectivity

Enables system design flexibility

Bend-improved fibre

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Corning® CleanAdvantage™ technology and optimised dust cap

Eliminates the need for scoping and cleaning prior to initial field connection

EDGE8® MTP® Trunk Cable Bend-improved single-mode (OS2), 8F MTP (pinned) Connector to 8F MTP (pinned) Connector, 8F, with 840 mm legs, no pulling grip, 30 m

CORNING

Specifications

Pulling grip - Connector B

Typical Force to Engage / Disengage FD	No
--	----

Furcation - Connector A

Furcation type	EDGE™ size 1, 14.7 mm x 14.7 mm x 108.6 mm
Leg colour	Yellow
Leg diameter	2 mm
Leg count	1
Plug Height	14.7 mm
Plug Width	14.7 mm
Plug Depth	108.6 mm
Leg Length	840 mm

Furcation - Connector B

Furcation type	EDGE™ size 1, 14.7 mm x 14.7 mm x 108.6 mm
Leg colour	Yellow
Leg diameter	2 mm
Leg count	1
Leg Length	840 mm

Environmental Conditions

Temperature range, operation	-10 °C to 60 °C
------------------------------	-----------------

Specifications - Connector B

Insertion loss, max.	0.35 dB
Boot colour	Black

EDGE8® MTP® Trunk Cable Bend-improved single-mode (OS2), 8F MTP (pinned) Connector to 8F MTP (pinned) Connector, 8F, with 840 mm legs, no pulling grip, 30 m

CORNING

Specifications - Connector B

Connector type	MTP® (pinned)
Ferrule material	Composite
Reflectance	≤ -65 dB

Dimensions

Length	30 m
--------	------

Mechanical Characteristics

Nominal outer diameter	5.5 mm
------------------------	--------

Design

Fibre count	8
Outer jacket colour	Yellow
Polarity	Universal, TIA-568 type-A

Specifications - Connector A

Insertion loss, max.	0.35 dB
Boot colour	Black
Connector type	MTP® (pinned)
Ferrule material	Composite
Reflectance	≤ -65 dB

Pulling grip - Connector A

Typical Force to Engage / Disengage FD	No
--	----

EDGE8® MTP® Trunk Cable Bend-improved single-mode (OS2), 8F MTP (pinned) Connector to 8F MTP (pinned) Connector, 8F, with 840 mm legs, no pulling grip, 30 m

CORNING

Ordering Information

Product Number	ZE7E708GLZDDU030M
Packing type	Plastic reel
Packing contents	2x EDGE™ clips size 1 single stack, 2x EDGE clips size 1 double stack, 2x EDGE U-clips size 1, a printed test report and SRP
Units per delivery	1/1

General Specifications

Cable assembly type	EDGE8® Trunk
Application	Data Centre LAN/SAN
Assembly Insertion Loss	Indoor: ANSI/ICEA S-83-596

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Optical Characteristics

Cable cutoff wavelength	1260 nm
Fibre code	E
Fibre name	E9/125 SMF28e+®
Fibre Type	Single-mode
Fibre core diameter	9 µm
Serial 1 gigabit ethernet	5000 MHz*km / - / -
Serial 10 gigabit ethernet	10000 MHz*km / - / 40000 MHz*km
Typical attenuation	0.38 dB/km / 0.38 dB/km / 0.25 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fibre category	OS2

EDGE8® MTP® Trunk Cable Bend-improved single-mode (OS2), 8F MTP (pinned) Connector to 8F MTP (pinned) Connector, 8F, with 840 mm legs, no pulling grip, 30 m



CORNING



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.