

CCH Module

Splicing, empty, for one CCH adapter panel

CORNING

CCH modules enable fast field termination and easy modular management of connectorisation within the housing.

The CCH splicing module supports fusion splicing of individual or ribbon fibres, with heat shrinks, pigtail slack and cable slack managed within a single space saving footprint. This eliminates the need for individual splice trays or separate splice housings, as well as allowing splicing to be done away from the rack housing in a suitable workspace as needed. The modular design makes it easy to access the fibre in an individual module without disturbing the other fibres in the housing. A CCH panel with the desired adapter configuration can be ordered separately and fits easily into the module.

A CCH termination and slack storage module option with no splice tray, suitable for use with field-installable connectors, is also available.

Each module is shipped with one rail for use with CCH-01U/2U/3U housings and two rails used with CCH-04U and the WCH-02P/4P/6P housings. Grommets and cable ties for strain relief and protective braided tubing for incoming cable are also included. Splicing modules ship with 12 single fibre heat-shrink splice protectors.



Features and Benefits

Manage cable slack for a CCH panel in a modular footprint

Fast, easy and reliable initial routing, and quick, simple reaccess for moves, adds and changes (MACs)

Splicing module holds 24 single fibre splices

Splice to full housing capacity, and manage all splices inside the housing

Includes everything needed to convert a CCH housing for modular routing and/or splicing

Easy ordering and field installation

Standards

Approvals and Listings

Meets ANSI/TIA/EIA-568A and 606

CCH Module

Splicing, empty, for one CCH adapter panel

CORNING

Specifications

General Specifications

Application	Enterprise Networks, Data Centre
Product type	Rack-Mountable Hardware
Mounting type	Rack 19", Rack 23", Wall-mount
Technology	Fusion Splice
Product category	Core product

Design - Hardware

Splice Protectors Type	Heat-shrink
Splice Tray Capacity Single Fiber	24
Splice Tray Capacity Mass Fusion	6
Panel or Module Type	CCH

Mechanical Characteristics

Dimensions (L x W x D)	162.0 mm x 35.0 mm x 200.0 mm (6.4 in x 1.4 in x 7.9 in)
------------------------	--

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	CCH-CS
Product Description	CCH Module, splicing, empty, for one CCH adapter panel
EAN Code	4056418168906

Shipping Information

Units Per Delivery	1/1
Dimensions (HxWxD)	5 cm x 20.3 cm x 36.8 cm (2 in x 8 in x 14.5 in)
Shipping Weight	0.5 kg (1.0 lb)

CCH Module

Splicing, empty, for one CCH adapter panel

The Corning logo consists of a solid blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

Notes



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.