

Plug & Play™ Universal Module, LC

Low-Loss, 24 fibres, Shuttered LC Duplex to MTP®, OM4

CORNING

The Plug & Play™ modules provide the interface between the MTP® on the trunk and the LC or SC duplex jumpers that will then connect directly into the electronics. The LC duplex adapters feature hinged VFL-compatible shutters that move up and out of the way when the connector is inserted. Specially designed indents in the shutters ensure that the end faces of the connectors are never touched. These shutters replace the standard dust caps that typically once removed are never replaced, exposing the interior end faces to dust particles and possible damage.

Features and Benefits

Connector modules

Allow for fibre modularity while offering both front and rear loading capability

Shuttered modules

Create one-hand operation while eliminating need to keep up with dust caps

Universal wired components

Enable moves, adds and changes without polarity concerns; provide a simple migration path between 2-fibre and parallel optic applications

Standard and low-loss components

Provide means of meeting increasingly stringent network performance requirements



Part Number: CCH-UM24-05-93Q

Specifications

General Specifications

Application	Data Centre LAN/SAN
Product type	Panels & Modules
Fibre Category	50 µm MM (OM4)

Design - Hardware

Fibre Count	24
Number of adapters per panel	12
Adapter Type Front	Shuttered LC
Adapter Colour Front	turquoise
Adapter Type Back	MTP®
Adapter Color Back	turquoise

Plug & Play™ Universal Module, LC

Low-Loss, 24 fibres, Shuttered LC Duplex to MTP®, OM4

CORNING

Optical Specification - Hardware

Insertion Loss	0.5 dB
----------------	--------

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	CCH-UM24-05-93Q
Product Description	Plug & Play™ Universal Module, LC, Low-Loss, 24 fibres, Shuttered LC Duplex to MTP®, OM4
EAN Code	4042673188537



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.