

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x8 G50 MMF ClearCurve® OM4 CT 3.0

CORNING

Part Number:
008TEU-13198A2G

The central tube cable construction, by isolating the fibres from installations and environmental rigors, provides stable and highly reliable transmission parameters. The fibres in are color coded for quick, easy identification.

The cable construction, based on a central buffer tube, is very compact, light and flexible, and ideal for connections requiring a moderate fiber count.

These cables are designed for installation in conduits, ducts and in-house.

Features and Benefits

All-dielectric cable construction

Requires no grounding or bonding

Laminated swelling glass yarns

Improved rodent resistance and longitudinal water protection

UV- and microbe-resistant

Can be installed in ducts or conduits

Small diameter and bend radius

Easy installation in space-constrained areas

Fibres colour coding to Telcordia-Bellcore

Easy identification of the individual fibres

Waterblocking technology



OSP (outdoor) applications

Silicon-free outer jacket

The cable jacket is free of harmful to paint structures

Flame retardant

LSZH™/FRNC



008TEU-13198A2G

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x8 G50 MMF ClearCurve® OM4 CT 3.0

CORNING

Specifications

Mechanical Specifications

Crush resistance	1500 N/10 cm
Min. bend radius installation	130 mm
Min. bend radius operation	100 mm
Nominal outer diameter	6.6 mm

Cable Design

Fibre count	8
Number of ripcords	1
Outer jacket colour	Black
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, zero-halogen (FRNC/LSZH) material
Outer jacket nominal thickness	1.2 mm
Tensile Strength Elements and/or Armouring - Layer 1	Laminated swelling glass yarn armour
Buffer tube diameter	3 mm
Fibre colouring	Blue, orange, green, brown, grey, white, red, black

Environmental Conditions

Temperature range, installation	-5 °C to 50 °C
Temperature range, storage	-25 °C to 70 °C
Temperature range, operation	-20 °C to 60 °C

General Specifications

Environment	Indoor/Outdoor
Cable type	Single Tube
Product type	Dielectric armour

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x8 G50 MMF ClearCurve® OM4 CT 3.0

CORNING

General Specifications

Fibre category	50 µm MM (OM4)
Flame rating	LSZH™/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	U-DQ(ZN)BH
Application	Duct , Vertical Riser , General Purpose Horizontal

Ordering Information

Weight	46 kg/km
--------	----------

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Waterblocking	IEC 60794-1-2 F5
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable)
Reaction to fire requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low Smoke to IEC 61034
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Optical Characteristics

Fibre code	T
Fibre name	G50/125 ULTRA-BEND 7.5
Fibre Type	Multimode
Fibre core diameter	50 µm
Minimum effective modal bandwidth (EMB)	4700 MHz*km / -
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Min. overfilled launch (OFL) bandwidth	3500 MHz*km / 500 MHz*km
Serial 1 gigabit ethernet	1100 MHz*km / 600 MHz*km
Serial 10 gigabit ethernet	550 MHz*km / -

Central Tube Dielectric Armour Indoor/Outdoor Cable 1x8 G50 MMF ClearCurve® OM4 CT 3.0

CORNING

Optical Characteristics

Typical attenuation	2.4 dB/km / 0.8 dB/km
Wavelengths	850 nm / 1300 nm
Fibre category	OM4



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2020 Corning Optical Communications. All rights reserved.